

VIVARIUM CAGE WASH ROOM CONTROL

SEQUENCE OF OPERATION

UNOCCUPIED MODE - THE BAS MODULATES THE REHEAT COIL VALVE TO MAINTAIN THE EXHAUST AIR TEMP AT SETPOINT AND SETS THE SUPPLY AIR FLOW TO ITS MINIMUM SETTING. THE EXHAUST AIR FLOW TRACKS THE SUPPLY AIR FLOW TO MAINTAIN ROOM PRESSUR

LIGHTING IS CONTROLLED VIA LOCAL TOGGLE SWITCHES (NOT SHOWN). BAS DOES NOT HAVE CONTROL OF LIGHTING

ROOM NO.	TEMP. SETPOINT	HUMIDITY SETPOINT	ROOM PRES.	CFM OFFSET
XXXX	72°F	40% R.H.	NEG.	150

M	JNIVERSITY OF MICHIGA
	ADCUITECTURE ENGINEERING AND CONCERNICE

ARCHITECTURE & ENGINEERING
326 East Hoover, Mail Stop B
Ann Arbor, MI 48109-1002
Phone: 734-764-3414
Fax: 734-936-3334

Abbreviated Documents

TERMS & CONDITIONS FOR DOCUMENT US

APPROVED BY			
REPRESENTING			
DRAWN BY	DESIGN MANAGER		
DESIGNED BY	REVIEWED BY		
$\overline{=}$			
:	•		
	•		
	<u> </u>		
•	<u> </u>		
•	•		
—: <u> </u>			
:			
:	•		
	•		
	•		
<u> </u>	•		
•	•		
— •			
: 			
— <u>:</u>			
I — . 			

Campus
University Of Michigan
Ann_Arbor_, MI

UNIVERSITY OF MICHIGAN
ARCHITECTURE, ENGINEERING AND CONSTRUCTION
326 East Hoover, Mail Stop E
Ann Arbor, Mil 45109-1002
Phone: 734-764-3414
Fax: 734-936-3334

100XXXX

P000XXXXX

Vivarium Cage Wash Room **Control Drawing**